

Product Data Sheet
Edition 18/07/2007
Identification no:
00 00 00 00 000 0 000000
Intraplast® N 200

Intraplast® N 200

Expanding grout admixture

Product Description	Intraplast® N 200 is an expanding grout admixture for pressure/injection grouting. By introducing into the concrete mix, wet volume expansion and increased fluidity without segregation are produced.
Uses	Intraplast® N 200 is used to increase flow and cohesion in cement grouts (addition of sand is possible) and to develop non-shrink property. This product can be used for grouting of: <ul style="list-style-type: none">■ Pre-stressed cable ducts■ Rock and soil anchoring■ Bearing plates■ Pre-placed aggregates■ Tunnel linings
Characteristics / Advantages	Intraplast® EP provides the following beneficial properties: <ul style="list-style-type: none">■ Improved fluidity■ Increased cohesion■ Volume expansion in the wet state to develop non-shrink property■ Chloride free - does not attack reinforcement or prestressed cables
Dispensing	Add directly to the cement / water mix in the mixer. Sand may be added as required.

Product Data

Form

Appearance / Colour Light brown powder

Packaging 12.5 kg bag

Storage

Storage Conditions / Shelf-Life 6 months from date of production if stored properly in dry conditions in undamaged and unopened original sealed packaging.

Technical Data

Chemical Base Modified naphthalene

Bulk Density ~0.80 kg/l at 27°C

Fluidity ~ 15-20 sec. (According to ASTM C 939 -87)



Mechanical / Physical Properties

Expansion	3-9 %	(According to ASTM C 937- 80)
-----------	-------	-------------------------------

System Information

Application Details

Dosage	0.40% by weight of cement (200 gm per 50 kg bag of cement).	
--------	---	--

Application Method / Tools	Add directly to the cement / water mix in the mixer. Sand may be added as required.	
----------------------------	---	--

Cleaning of Tools	Clean all tools and application equipment with water immediately after use. Hardened/cured material can only be mechanically removed.	
-------------------	---	--

Value Base	All technical data stated in this Product Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.	
------------	--	--

Health and Safety Information	For information and advice on the safe handling, storage and disposal of chemical products, users shall refer to the most recent Material Safety Data Sheet containing physical, ecological, toxicological and other safety-related data.	
-------------------------------	---	--

Legal Notes	<p>The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.</p>	
-------------	---	--

