

S-Termination Bar III



Overview S-Termination Bar III is 2.0 mm thick aluminum alloy strip with one side bending edge for membrane termination.

Properties	Material	Aluminum alloy
	Colour	Silvery white
	Dimension (mm)	2m L x 35mm W
	Hole diameter (mm)	6.5 @100

Application S-Termination Bar III is used for termination of PVC membranes on upstand that has no grooves or extrusions. Fastener nail head should be at least 7mm. Sarnafil sealant shall be used to seal the gap between termination bar and upstand.

Packaging 50 pcs (100m) / bundle

Sika India Pvt. Ltd.
620, Diamond Harbour Road, Kolkata, 700 034, India

Tel: +91 33 2447 2448/2449
Fax: +91 33 2468 8688/2665
E-mail: info@in.sika.com
Website: www.sika.in

All data in our product information are based on our current knowledge and experience. They do not release users from careful testing of the application and strict observation of the relevant processing regulations because of the wide range of possible influences during the application and use of our products. Legally valid assurances of specific characteristics or suitability for special purposes of application other than those provided in our documentation for the specific product cannot be inferred from our information. The recipient or processor of our products at their own responsibility must follow any protective rights or existing laws and provisions. Moreover our general terms and conditions of sale and warranty are valid.