

## S-Welding Cord



**Overview** S-Welding Cord is a hot air weldable PVC cord.

### Properties

<b>Material</b>	PVC dry blend
<b>Colour</b>	Light grey
<b>Dimension (mm)</b>	Diameter - 4

**Application** S-Welding cord is welded to the membrane using special welding nozzle along S-U Bar to resist pull forces (like wind up-lift) towards roof centre as reinforced perimeter fixation. It helps to distribute the load evenly and prevent slippage of the membrane.

**Packaging** 300 m / barrel

#### Sika India Pvt. Ltd.

620, Diamond Harbour Road, Kolkata, 700 034, India

Tel: +91 33 2447 2448/2449

Fax: +91 33 2468 8688/2665

E-mail: [info@in.sika.com](mailto:info@in.sika.com)

Website: [www.sika.in](http://www.sika.in)

All data in our product information are based on our current knowledge and experience. They do not release users from careful testing of the application and strict observation of the relevant processing regulations because of the wide range of possible influences during the application and use of our products. Legally valid assurances of specific characteristics or suitability for special purposes of application other than those provided in our documentation for the specific product cannot be inferred from our information. The recipient or processor of our products at their own responsibility must follow any protective rights or existing laws and provisions. Moreover our general terms and conditions of sale and warranty are valid.